

| Model | | Indoor | CS-E12NKEW, CS-XE12NKEW | | | CS-E15NKEW, CS-XE15NKEW | | |
|--|---|-------------------------|-------------------------|---------------------|-------------------------|-------------------------|---------------------|-------|
| | | Outdoor | CU-E12NKE | | | CU-E15NKE | | |
| Performance Test Condition | | | EUROVENT | | | EUROVENT | | |
| Power Supply | | Phase, Hz | Single, 50 | | | Single, 50 | | |
| | | V | 230 | | | 230 | | |
| | | | Min. | Mid. | Max. | Min. | Mid. | Max. |
| Cooling | Capacity | kW | 0.85 | 3.50 | 4.00 | 0.85 | 4.20 | 5.00 |
| | | BTU/h | 2900 | 11900 | 13600 | 2900 | 14300 | 17100 |
| | | Kcal/h | 730 | 3010 | 3440 | 730 | 3610 | 4300 |
| | Running Current | A | - | 4.0 | - | - | 5.7 | - |
| | Input Power | W | 250 | 855 | 1.13k | 260 | 1.26k | 1.57k |
| | Annual Consumption | kWh | - | 428 | - | - | 630 | - |
| | EER | W/W | 3.40 | 4.09 | 3.54 | 3.27 | 3.33 | 3.18 |
| | | BTU/hW | 11.60 | 13.92 | 12.04 | 11.15 | 11.35 | 10.89 |
| | | Kcal/hW | 2.92 | 3.52 | 3.04 | 2.81 | 2.87 | 2.74 |
| | Power Factor | % | - | 93 | - | - | 96 | - |
| | Indoor Noise (H / L / QLo) | dB-A | 42 / 28 / 20 | | | 43 / 31 / 25 | | |
| | | Power Level dB | 58 / - | | | 59 / - | | |
| | Outdoor Noise (H / L) | dB-A | 48 / - | | | 49 / - | | |
| | | Power Level dB | 63 / - | | | 64 / - | | |
| Heating | Capacity | kW | 0.85 | 4.00 | 6.00 | 0.85 | 5.30 | 6.80 |
| | | BTU/h | 2900 | 13600 | 20500 | 2900 | 18100 | 23200 |
| | | Kcal/h | 730 | 3440 | 5160 | 730 | 4560 | 5850 |
| | Running Current | A | - | 4.3 | - | - | 6.6 | - |
| | Input Power | W | 245 | 930 | 1.71k | 255 | 1.44k | 1.94k |
| | COP | W/W | 3.47 | 4.30 | 3.51 | 3.33 | 3.68 | 3.51 |
| | | BTU/hW | 11.84 | 14.62 | 11.99 | 11.37 | 12.57 | 11.96 |
| | | Kcal/hW | 2.98 | 3.70 | 3.02 | 2.86 | 3.17 | 3.02 |
| | Power Factor | % | - | 94 | - | - | 95 | - |
| | Indoor Noise (H / L / QLo) | dB-A | 42 / 33 / 20 | | | 43 / 35 / 29 | | |
| | | Power Level dB | 58 / - | | | 59 / - | | |
| | Outdoor Noise (H / L) | dB-A | 50 / - | | | 51 / - | | |
| | | Power Level dB | 65 / - | | | 66 / - | | |
| | Low Temp. : Capacity (kW) / I.Power (W) / COP | | | 4.47 / 1.48k / 3.02 | | | 4.92 / 1.72k / 2.86 | |
| Extr Low Temp. : Capacity (kW) / I.Power (W) / COP | | | 3.37 / 1.49k / 2.26 | | | 4.11 / 1.73k / 2.38 | | |
| Max Current (A) / Max Input Power (W) | | | 7.8 / 1.71k | | | 9.0 / 1.94k | | |
| Starting Current (A) | | | 4.3 | | | 6.6 | | |
| Compressor | Type | Hermetic Motor (Rotary) | | | Hermetic Motor (Rotary) | | | |
| | Motor Type | Brushless (6-poles) | | | Brushless (6-poles) | | | |
| | Output Power | W | 700 | | | 700 | | |