

Model		Indoor	CS-E12PKEW, CS-XE12PKEW			CS-E15PKEW, CS-XE15PKEW				
		Outdoor	CU-E12PKE			CU-E15PKE				
Performance Test Condition			EUROVENT			EUROVENT				
Power Supply		Phase, Hz	Single, 50			Single, 50				
		V	230			230				
			Min.	Mid.	Max.	Min.	Mid.	Max.		
Cooling	Capacity		kW	0.85	3.50	4.00	0.85	4.20	5.00	
			BTU/h	2900	11900	13600	2900	14300	17100	
			Kcal/h	730	3010	3440	730	3610	4300	
	Running Current		A	-	3.8	-	-	5.5	-	
	Input Power		W	250	850	1.12k	260	1.25k	1.55k	
	Annual Consumption		kWh	-	425	-	-	625	-	
	EER		W/W	3.40	4.12	3.57	3.27	3.36	3.23	
			BTU/hW	11.60	14.00	12.14	11.15	11.44	11.03	
			Kcal/hW	2.92	3.54	3.07	2.81	2.89	2.77	
	ErP	Pdesign		kW	3.5			4.2		
		SEER		(W/W)	6.6			5.9		
		Annual Consumption		kWh	186			249		
		Class			A++			A+		
	Power Factor		%	-	97	-	-	99	-	
	Indoor Noise (H / L / QLo)		dB-A	42 / 28 / 20			43 / 31 / 25			
			Power Level dB	58 / -			59 / -			
	Outdoor Noise (H / L)		dB-A	48 / -			49 / -			
			Power Level dB	63 / -			64 / -			
	Heating	Capacity		kW	0.85	4.00	6.00	0.85	5.30	6.80
				BTU/h	2900	13600	20500	2900	18100	23200
Kcal/h				730	3440	5160	730	4560	5850	
Running Current		A	-	4.1	-	-	6.4	-		
Input Power		W	245	925	1.69k	255	1.43k	1.93k		
COP		W/W	3.47	4.32	3.55	3.33	3.71	3.52		
		BTU/hW	11.84	14.70	12.13	11.37	12.66	12.02		
		Kcal/hW	2.98	3.72	3.05	2.86	3.19	3.03		
ErP		Pdesign		kW	3.2			3.6		
		Tbivalent		°C	-10			-10		
		SCOP		(W/W)	4.0			3.6		
		Annual Consumption		kWh	1120			1400		
		Class			A+			A		
Power Factor		%	-	98	-	-	97	-		
Indoor Noise (H / L / QLo)		dB-A	42 / 33 / 20			43 / 35 / 29				
		Power Level dB	58 / -			59 / -				
Outdoor Noise (H / L)		dB-A	50 / -			51 / -				
		Power Level dB	65 / -			66 / -				
Low Temp. : Capacity (kW) / I.Power (W) / COP			4.47 / 1.46k / 3.06			4.92 / 1.71k / 2.88				
Extr Low Temp. : Capacity (kW) / I.Power (W) / COP			3.37 / 1.47k / 2.29			4.11 / 1.72k / 2.39				
Max Current (A) / Max Input Power (W)			7.6 / 1.69k			8.8 / 1.92k				
Starting Current (A)			4.1			6.4				