

Model	Indoor	CS-E7NKEW, CS-XE7NKEW			CS-E9NKEW, CS-XE9NKEW			
	Outdoor	CU-E7NKE-3			CU-E9NKE-3			
Performance Test Condition		EUROVENT			EUROVENT			
Power Supply	Phase, Hz	Single, 50			Single, 50			
	V	230			230			
		Min.	Mid.	Max.	Min.	Mid.	Max.	
Cooling	Capacity	kW	0.75	2.05	2.40	0.85	2.50	3.00
		BTU/h	2560	6990	8180	2900	8530	10200
		Kcal/h	650	1760	2060	730	2150	2580
	Running Current	A	-	2.2	-	-	2.5	-
	Input Power	W	240	470	580	245	535	730
	Annual Consumption	kWh	-	235	-	-	268	-
	EER	W/W	3.13	4.36	4.14	3.47	4.67	4.11
		BTU/hW	10.67	14.87	14.10	11.84	15.94	13.97
		Kcal/hW	2.71	3.74	3.55	2.98	4.02	3.53
	Power Factor	%	-	93	-	-	93	-
	Indoor Noise (H / L / QLo)	dB-A	37 / 24 / 20			39 / 25 / 20		
		Power Level dB	53 / -			55 / -		
	Outdoor Noise (H / L)	dB-A	45 / -			46 / -		
		Power Level dB	60 / -			61 / -		
	Heating	Capacity	kW	0.75	2.80	4.00	0.85	3.40
BTU/h			2560	9550	13600	2900	11600	17100
Kcal/h			650	2410	3440	730	2920	4300
Running Current		A	-	3.0	-	-	3.4	-
Input Power		W	230	635	1.02k	240	735	1.30k
COP		W/W	3.26	4.41	3.92	3.54	4.63	3.85
		BTU/hW	11.13	15.04	13.33	12.08	15.78	13.15
		Kcal/hW	2.83	3.80	3.37	3.04	3.97	3.31
Power Factor		%	-	92	-	-	94	-
Indoor Noise (H / L / QLo)		dB-A	38 / 25 / 20			40 / 27 / 20		
		Power Level dB	54 / -			56 / -		
Outdoor Noise (H / L)		dB-A	46 / -			47 / -		
		Power Level dB	61 / -			62 / -		
Low Temp. : Capacity (kW) / I.Power (W) / COP		2.90 / 900 / 3.22			3.62 / 1.15k / 3.15			
Extr Low Temp. : Capacity (kW) / I.Power (W) / COP		2.35 / 930 / 2.53			2.88 / 1.18k / 2.44			
Max Current (A) / Max Input Power (W)		4.7 / 1.02k			5.8 / 1.30k			
Starting Current (A)		3.0			3.4			
Compressor	Type	Hermetic Motor (Rotary)			Hermetic Motor (Rotary)			
	Motor Type	Brushless (6-poles)			Brushless (6-poles)			
	Output Power	W	650			700		