

SPLIT DE PARED 1x1

Serie MF2 ECO



- Funciona hasta -7°C
- Filtro biológico antiolores
- Modo nocturno
- Rearme automático
- Reducidas dimensiones



INVERTER DC

Código		CL19691	CL19692	CL19693	CL19694
Modelo		FW2-2250-ECO	FW2-3000-ECO	FW2-3000-ECO KIT	FW2-3000-INV-ECO
	EAN	8432953007485	8432953007492	8432953007508	8432953007515
Capacidad Refrigeración	W	2490	3200	3200	3300(1400-3520)
Potencia absorbida Frio	W	776	997	997	1028(450-1500)
Corriente Frio	A	3,37	4,34	4,34	4.5(2.0-7.5)
EER	W/W	3,21	3,21	3,21	3,21
Capacidad Calefacción	W	2640	3350	3350	3500(1100-3750)
Potencia absorbida Calor	W	742	928	928	969(400-1350)
Corriente Calor	A	3,48	4,05	4,05	4.22(1.6-7.0)
COP	W/W	3,56	3,61	3,61	3,61
Corriente Máxima	A	5,0	8,0	8,0	8,5
Potencia Máxima	W	1134	1580	1580	2100
Carga de refrigerante	g	390	800	800	830
Caudal de aire	m ³ /h	400	520	520	530
Nivel Sonoro	dB(A)	38/51	37/50	37/50	43/52
Peso neto Ud. Interior	Kg	7,5	9	9	11/9.5
Peso neto Ud. Exterior	Kg	21	29	29	36/33
Compresor		GMCC	GMCC	GMCC	GMCC
Dimensión neta	mm	680x250x180	745x250x210	745x250x210	802x265x190
Dimensión embalaje	mm	740x310x250	800x320x280	800x320x280	860x325x255
Dimensión neta	mm	600x490x250	760x260x540	760x260x540	760x260x540
Dimensión embalaje	mm	730x500x370	880x370x600	880x370x600	880x370x600