

PIXMA Printers Specifications Chart	PIXMA iP5200	PIXMA iP5200R
Resolution	Up to 9600 x 2400 dpi ¹	Up to 9600 x 2400 dpi ¹
Print Engine	5-ink FINE print head with 1 pl Micro-Nozzles	5-ink FINE print head with 1 pl Micro-Nozzles
Colour Management	ICM, ColorSync, Exif Print	ICM, ColorSync, Exif Print
Photo Print Speed	Borderless 10 x 15cm: Approx. 36 seconds A4: Up to 43 seconds (Max.)	Borderless 10 x 15cm: Approx. 36 seconds A4: Up to 43 seconds (Max.)
Mono Print Speed	Up to 30ppm (Max.), 15ppm (Std)	Up to 30ppm (Max.), 15ppm (Std)
Colour Print Speed	Text & Graphics: Up to 24ppm (Max.), 11.7ppm (Std) A4 Full Page: Approx. 19 seconds (Std)	Text & Graphics: Up to 24ppm (Max.), 11.7ppm (Std) A4 Full Page: Approx. 19 seconds (Std)
Media Type	See Media Compatibility Worksheet	See Media Compatibility Worksheet
Media Weight	Sheet feeder: 64 to 105 g/m ² and supported Canon special media up to 273 g/m ²	Sheet feeder: 64 to 105 g/m ² and supported Canon special media up to 273 g/m ²
Media Input	Sheet feeder: 150 sheets, Cassette: 150 sheets CD-R / DVD tray: 1 printable CD-R or DVD	Sheet feeder: 150 sheets, Cassette: 150 sheets CD-R / DVD tray: 1 printable CD-R or DVD
DVD/CD Printing	Available as standard	Available as standard
Media Size	Sheet feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, Credit Card (54 x 86mm) Cassette: A4, B5, A5, Letter, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm	Sheet feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, Credit Card (54 x 86mm) Cassette: A4, B5, A5, Letter, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm
Borderless Printing	Available using Photo Paper Pro (A4 & 10 x 15cm), Photo Paper Plus Glossy (A4, 10 x 15cm, & 13 x 18cm), Photo Paper Plus Semi Gloss (A4 & 10 x 15cm), Glossy Photo Paper (A4, 10 x 15cm & Credit Card), Matte Photo Paper (A4, & 10 x 15cm)	Available using Photo Paper Pro (A4 & 10 x 15cm), Photo Paper Plus Glossy (A4, 10 x 15cm, & 13 x 18cm), Photo Paper Plus Semi Gloss (A4 & 10 x 15cm), Glossy Photo Paper (A4, 10 x 15cm & Credit Card), Matte Photo Paper (A4, & 10 x 15cm)
Two Sided Printing	Automatically selectable using Photo Paper Plus Double Sided or plain paper in A4, B5, A5, Letter & 13 x 18cm	Automatically selectable using Photo Paper Plus Double Sided or plain paper in A4, B5, A5, Letter & 13 x 18cm
Ink Cartridge Configuration	Single Ink technology – 5 separate ink tanks (PGI-5BK, CLI-8BK, CLI-8C, CLI-8M & CLI-8Y)	Single Ink technology – 5 separate ink tanks (PGI-5BK, CLI-8BK, CLI-8C, CLI-8M & CLI-8Y)
Black Ink Tank Life	PGI-5BK: 360 pages at 5 % coverage ² PGI-5BK: 1250 pages (Printing ISO/JIS-SCID N5) ³	PGI-5BK: 360 pages at 5 % coverage ² PGI-5BK: 1250 pages (Printing ISO/JIS-SCID N5) ³
Colour Ink Tank(s) Life	420 pages at 5% coverage per ink tank ² Cyan: 710 pages, Magenta: 500 pages, Yellow: 480 pages, (Printing ISO/JIS-SCID N5) ³	420 pages at 5% coverage per ink tank ² Cyan: 710 pages, Magenta: 500 pages, Yellow: 480 pages, (Printing ISO/JIS-SCID N5) ³
PC Interface & Connectivity	USB 2.0Hi-Speed ⁶	USB 2.0 ⁶ Hi-Speed, Wi-Fi: IEEE 802.11g/b, Ethernet: 100BASE-TX,10BASE-T
Camera Interface & Connectivity	Direct Print Port: Camera direct photo printing from PictBridge & Bubble Jet Direct compliant digital cameras & camcorders	Direct Print Port: Camera direct photo printing from PictBridge & Bubble Jet Direct compliant digital cameras & camcorders
Camera Direct Printing	Compatibility: Exif 2.2 or earlier, DPOF compliant	Compatibility: Exif 2.2 or earlier, DPOF compliant
Image Viewer		
Operating System Requirements	Windows: PC with Windows XP, Windows 2000, Windows Me or Windows 98, USB interface ⁵ , CD-ROM Drive. Free hard disk space: 370 MB for Windows XP/2000 and Windows Me/98. Mac: Macintosh computer with Mac OS X v10.2.1 or later, USB interface. Free hard disk space: 350 MB for Mac OS X v10.2.1 or later.	Windows: PC with Windows XP, Windows 2000, Windows Me or Windows 98, USB interface ⁵ , CD-ROM Drive. Free hard disk space: 370 MB for Windows XP/2000 and Windows Me/98. Mac: Macintosh computer with Mac OS X v10.2.1 or later, USB interface. Free hard disk space: 350 MB for Mac OS X v10.2.1 or later.
Driver Features	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac: Photo Optimizer PRO, Vivid Photo, Photo Noise Reduction	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac: Photo Optimizer PRO, Vivid Photo, Photo Noise Reduction

Software Included	Windows: Easy-WebPrint, Easy-PhotoPrint, PhotoRecord, Easy-PrintToolBox and CD-LablePrint. Mac: Easy-PhotoPrint and CD-LabelPrint	Windows: Easy-WebPrint, Easy-PhotoPrint, PhotoRecord, Easy-PrintToolBox and CD-LablePrint. Mac: Easy-PhotoPrint and CD-LabelPrint
Power Source	AC 220 – 240V 50 – 60Hz	AC 220 – 240V 50 – 60Hz
Power Consumption	Approx. 0.8W (standby), approx. 17W (printing)	Approx. 4.5W (standby), approx. 19W (printing)
Operating Temperature Range	5° – 35° C	5° – 35° C
Operating Humidity	10 – 90% RH (no condensation)	10 – 90% RH (no condensation)
Acoustic Noise Levels	Approx. 34.7dB (A) (best quality mode)	Approx. 34.7dB (A) (best quality mode)
Dimensions (W x D x H)	444 x 309 x 160mm	444 x 309 x 160mm
Weight	Approx. 7.3kg	Approx. 7.5kg

Footnotes

1	Ink droplets can be placed with a minimum pitch of 1/9600 inch	Ink droplets can be placed with a minimum pitch of 1/9600 inch
2	Print volume figures may vary with the content of the document and the print mode. Black calculation based on an average of four printers run continuously until ink out printing 1500 characters per page, normal text, in default mode on plain paper using Windows XP and Word 2003.	Print volume figures may vary with the content of the document and the print mode. Black calculation based on an average of four printers run continuously until ink out printing 1500 characters per page, normal text, in default mode on plain paper using Windows XP and Word 2003.
3	Print volume figures may vary with the content of the document and the print mode. Colour calculation based on an average of four printers run continuously until ink out printing the ISO/JIS-SCID N5 pattern in default mode on plain paper using Windows XP and Photoshop 7.0	Print volume figures may vary with the content of the document and the print mode. Colour calculation based on an average of four printers run continuously until ink out printing the ISO/JIS-SCID N5 pattern in default mode on plain paper using Windows XP and Photoshop 7.0
4	Using recommended adaptor – not supplied.	Using recommended adaptor – not supplied.
5	USB operation can only be guaranteed on a PC with pre-installed Windows XP, Windows 2000, Windows Me or Windows 98.	USB operation can only be guaranteed on a PC with pre-installed Windows XP, Windows 2000, Windows Me or Windows 98.
6	USB operation can only be guaranteed on a PC with pre-installed Windows XP, Windows 2000, Windows Me, or Windows 98. USB 2.0 Hi-Speed performance requires Windows XP Service Pack 1, Windows 2000 Service Pack 4 or Mac OS X version 10.2.7 or later with pre-installed USB 2.0 port.	USB operation can only be guaranteed on a PC with pre-installed Windows XP, Windows 2000, Windows Me, or Windows 98. USB 2.0 Hi-Speed performance requires Windows XP Service Pack 1, Windows 2000 Service Pack 4 or Mac OS X version 10.2.7 or later with pre-installed USB 2.0 port.

Common footnotes for all products

10x15cm borderless photo speed based on default
Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used and does not take into account data processing time on host computer.

All specifications subject to change without notice.
Print speeds may vary with computer system specifications and content of document printed.
Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. All brand and product names are trademarks of their respective companies.